

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

1 Identification

- · Product Identifier
- · Trade Name: Rub 'n Restore Color I
- Relevant identified uses of the substance or mixture and uses advised against:

Water-based coating to restore or recolor leather or vinyl

· Product Description:

Available colors: Ash, Bright White, Beige, Buckskin, Butterscotch, Camel, Clay, Ivory, Lagoon, Marine White, Midnight Blue, Pebble, Peppercorn, Pine, Sand, Sea Foam, Slate, Smoke, Stone, Storm Blue, Taupe, Walnut, Wine, Custom Color

- · Details of the Supplier of the Safety Data Sheet:
- · Manufacturer/Supplier:

Rub 'n Restore, Inc. 39585 Lund Rd. PO Box 1149 Paonia, CO 81428 rubnrestore.com 888-704-5571

· Emergency telephone number: 970-527-9508 - Lesandre Barley

2 Hazard(s) Identification

· Classification of the substance or mixture:



Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.



Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.

Eye Irritation 2A H319 Causes serious eye irritation.

- · Label elements:
- · Hazard pictograms:





- · Signal word: Warning
- · Hazard-determining components of labeling:

Titanium Oxide

1,2,4-Trimethylbenzene

2-butoxyethanol

Solvent naphtha (petroleum), light aromatic

· Hazard statements:

H332 Harmful if inhaled.


H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

· Precautionary statements:

P201 Obtain special instructions before use.





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

6 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 0

REACTIVITY O Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known


3 Composition/Information on Ingredients

· Non-hazardous components:	
7732-18-5 Water, distilled water, deionized water	25-50%

- · Chemical characterization: Substance
- · **Description:** Mixture of substances listed below with non-hazardous additions.

	Dangerous Components:		
	CAS: 13463-97-7	Titanium Oxide	25-50%
		♦ Carcinogenicity 2, H351	
	CAS: 7727-43-7	barium sulphate, natural	2-12%
	RTECS: CR 0600000		
	CAS: 25322-68-3	Polyethylene Glycol	≤2.5%
	CAS: 95-63-6	1,2,4-Trimethylbenzene	≤2.5%
	RTECS: DC3325000	Flammable Liquids 3, H226; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	
H	CAS: 107-98-2	1-methoxy-2-propanol	≤2.5%
	RTECS: UB 7700000	Flammable Liquids 3, H226; Specific Target Organ Toxicity - Single Exposure 3, H336	
		/0	

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

CAS: 111-76-2 RTECS: KJ 8575000	2-butoxyethanol Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Eye Irritation 2A, H319; Flammable Liquids 4, H227	≤2.5%
CAS: 111-90-0 RTECS: KK 8750000	Diethylene glycol monoethyl ether Skin Irritation 2, H315; Flammable Liquids 4, H227; Eye Irritation 2B, H320	≤2.5%
CAS: 64742-95-6	Solvent naphtha (petroleum), light aromatic Flammable Liquids 3, H226; Sapiration Hazard 1, H304; Acute Toxicity - Inhalation 4, H332	≤2.5%
CAS: 98-82-8 RTECS: GR 8575000	Cumene ♦ Flammable Liquids 3, H226; ♦ Acute Toxicity - Inhalation 3, H331; \$ Carcinogenicity 2, H351; Aspiration Hazard 1, H304; ♦ Acute Toxicity - Oral 4, H302; Specific Target Organ Toxicity - Single Exposure 3, H335	≤2.5%

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in the side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eve contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

Rinse opened eye for several minutes under running water.


- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- · Special hazards arising from the substance or mixture: No further relevant information available.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

- · Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Not required.
- Environmental precautions: Dilute with plenty of water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections:


See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:	13 for disposal information.	
7727-43-7	barium sulphate, natural	15 mg/m³
25322-68-3	Polyethylene Glycol	30 mg/m³
95-63-6	1,2,4-Trimethylbenzene	140 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
111-76-2	2-butoxyethanol	60 ppm
111-90-0	Diethylene glycol monoethyl ether	75 ppm
14808-60-7	Quartz (SiO2)	0.075 mg/m ³
98-82-8	Cumene	50 ppm
107-21-1	Ethylene glycol	30 ppm
PAC-2:		
7727-43-7	barium sulphate, natural	170 mg/m³
25322-68-3	Polyethylene Glycol	1,300 mg/m³
95-63-6	1,2,4-Trimethylbenzene	360 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
111-76-2	2-butoxyethanol	120 ppm
111-90-0	Diethylene glycol monoethyl ether	100 ppm
14808-60-7	Quartz (SiO2)	33 mg/m³
98-82-8	Cumene	300 ppm
107-21-1	Ethylene glycol	150 ppm
· PAC-3:		
7727-43-7	barium sulphate, natural	990 mg/m³
25322-68-3	Polyethylene Glycol	7,700 mg/m ³
95-63-6	1,2,4-Trimethylbenzene	480 ppm
107-98-2	1-methoxy-2-propanol	660 ppm
111-76-2	2-butoxyethanol	700 ppm
111-90-0	Diethylene glycol monoethyl ether	450 ppm

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

14808-60-7	Quartz (SiO2)	200 mg/m ³
98-82-8	Cumene	730 ppm
107-21-1	Ethylene glycol	900 ppm

7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- Components with occupational exposure limits:


The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

7727-43-7 barium sulphate, natural PEL Long-term value: 15* 5** mg/m³ *total dust **respirable fraction REL Long-term value: 10* 5** mg/m³ *total dust **respirable fraction TLV Long-term value: 5* mg/m³ *inhalable fraction; E 25322-68-3 Polyethylene Glycol WEEL Long-term value: 10 mg/m³ (H); MW>200 95-63-6 1,2,4-Trimethylbenzene REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 10 ppm A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm Long-term value: 50 ppm A4		, I		
*total dust **respirable fraction REL Long-term value: 10* 5** mg/m³ *total dust **respirable fraction TLV Long-term value: 5* mg/m³ *inhalable fraction; E 25322-68-3 Polyethylene Glycol WEEL Long-term value: 10 mg/m³ (H); MW>200 95-63-6 1,2,4-Trimethylbenzene REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 10 ppm A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm	7727-4	3-7 barium sulphate, natural		
*total dust **respirable fraction TLV Long-term value: 5* mg/m³ *inhalable fraction; E 25322-68-3 Polyethylene Glycol WEEL Long-term value: 10 mg/m³ (H); MW>200 95-63-6 1,2,4-Trimethylbenzene REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 10 ppm A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm Long-term value: 100 ppm Long-term value: 50 ppm	PEL			
*inhalable fraction; E 25322-68-3 Polyethylene Glycol WEEL Long-term value: 10 mg/m³ (H); MW>200 95-63-6 1,2,4-Trimethylbenzene REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 10 ppm A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm Long-term value: 100 ppm Long-term value: 50 ppm	REL			
WEEL Long-term value: 10 mg/m³ (H); MW>200 95-63-6 1,2,4-Trimethylbenzene REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 10 ppm A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm	TLV			
(H); MW>200 95-63-6 1,2,4-Trimethylbenzene REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 10 ppm A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm	25322-	68-3 Polyethylene Glycol		
REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 10 ppm A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm	WEEL			
TLV Long-term value: 10 ppm A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm	95-63-	6 1,2,4-Trimethylbenzene		
A4 107-98-2 1-methoxy-2-propanol REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm	REL	Long-term value: 125 mg/m³, 25 ppm		
REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm	TLV			
Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm	107-98	-2 1-methoxy-2-propanol		
Long-term value: 50 ppm	REL			
	TLV	Long-term value: 50 ppm		

(Contd. on page 6)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

111-76	3-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin	
REL	Long-term value: 24 mg/m³, 5 ppm Skin	
TLV	Long-term value: 20 ppm BEI, A3	
111-90	0-0 Diethylene glycol monoethyl ether	
WEEL	Long-term value: 25 ppm	
98-82-	8 Cumene	
PEL	Long-term value: 245 mg/m³, 50 ppm Skin	
REL	Long-term value: 245 mg/m³, 50 ppm Skin	
TLV	Long-term value: 5 ppm A3	
· Ingred	lients with biological limit values:	
111-76	6-2 2-butoxyethanol	
BEI 20	00 mg/g creatinine	
ur	ine	
er	nd of shift	
B	utoxyacetic acid (BAA) (with hydrolysis)	

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- Personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.


- · Breathing equipment: Not required.
- Protection of hands:



- · Material of gloves: Not applicable.
- · Penetration time of glove material: Not applicable.

(Contd. on page 7)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

· Eye protection:



Safety glasses recommended.



Tightly sealed goggles

· Limitation and supervision of exposure into the environment: None

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: Various colors
Odor: Odorless
Odor threshold: Not determined.

pH-value: Not applicable.

Change in condition

Melting point/Melting range: Not determined.

Boiling point/Boiling range: ≥100 °C (≥212 °F)

· Flash point: None

Flammability (solid, gaseous): Not applicable.
 Auto igniting: Not applicable
 Decomposition temperature: Not determined.

· *Ignition temperature:* Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

• Explosion limits:

Lower: Not determined. Upper: Not determined.

· *Vapor pressure* @ **20** °C (68 °F): ≤23 hPa (≤17.3 mm Hg)

• **Density @ 20 °C (68 °F):** ≥2.3211-≤2.3233 g/cm³ (≥19.3696-≤19.3879 lbs/gal)

Relative density: Not determined.
Vapor density: Not determined.
Evaporation rate: Not determined.

· Solubility in / Miscibility with:


Water: Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

Kinematic: Not determined.

· Solvent content:

 Organic solvents:
 6.1 %

 Water:
 45.6 %

 VOC content:
 6.19 %

 Solids content:
 44.0 %

· Other information: No further relevant information available.

10 Stability and Reactivity


- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

	· LD/LC50 values that are relevant for classification:		
13463-97-	13463-97-7 Titanium Oxide		
Dermal	LD50	>5,000 mg/kg (Rat)	
Inhalative	LC50/4 h	6.82 mg/l (Rat)	
25322-68-	3 Polyethylene	Glycol	
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Inhalative	LC50/96 hours	10,000 mg/l (Fish - Poecilia reticulate, 96h)	
95-63-6 1,	2,4-Trimethylbe	enzene	
Oral	LD50	6,000 mg/kg (Rat)	
Inhalative	LC50/96 hours	3.359 mg/l (Trout)	
	LC50/48 hrs	2.21 mg/l (Daphnia)	
107-98-2 1	107-98-2 1-methoxy-2-propanol		
Oral	LD50	5,660 mg/kg (Rat)	
	LD50	13,000 mg/kg (rabbit)	
Inhalative	LC50/96 hours	12,732 mg/l (Trout)	
	LC50/48 hrs	5,744 mg/l (Daphnia)	
111-76-2 2	2-butoxyethano		
Oral	LD50	1,200 mg/kg (ATE)	
		470 mg/kg (Rat)	
Dermal	LD50	220 mg/kg (rab)	
Inhalative	LC50/4 h	3 mg/l (ATE)	
		2,174.91 mg/l (Rat)	

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

111-90-0 I	Diethylene glyc	ol monoethyl ether
Oral	LD50	5,500 mg/kg (Rat)
Dermal	LD50	8,500 mg/kg (rabbit)
64742-95-	6 Solvent naph	tha (petroleum), light aromatic
Oral	LD50	>6,800 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (Rat)
98-82-8 C	umene	
Oral	LD50	1,400 mg/kg (Rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)
	LC50/96 hours	6.265 mg/l (Trout)
	LC50/48 hrs	3.202 mg/l (Daphnia)

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

111-76-2	2-butoxyethanol	3
14808-60-7	Quartz (SiO2)	1
98-82-8	Cumene	2B
· NTP (Nation	al Toxicology Program):	·
14808-60-7	Quartz (SiO2)	K
98-82-8	Cumene	R
· OSHA-Ca (C	Occupational Safety & Health Administration):	·
None of the	ngredients are listed.	


12 Ecological Information

· Toxicity:

· Aquatic toxicity:	
95-63-6 1,2,4-Trimethylbenzene	
EC50 3.084 mg/l (Green algae)	

(Contd. on page 10)





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

107-9	8-2 1-methoxy-2-propanol
EC50	1,654 mg/l (Green algae) (96 hr)
111-7	6-2 2-butoxyethanol
EC50	1,815 mg/l (Water flea)
98-82	-8 Cumene
EC50	4.148 mg/l (Green algae)

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household waste. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packaging
- · **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport Information

· UN-Number:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

Transport hazard class(es):

· DOT, ADR/ADN, ADN, IMDG, IATA

· Class: Non-Regulated Material

Packing group:

· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material

• Environmental hazards: Not applicable. Special precautions for user: Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.


· UN "Model Regulation": Non-Regulated Material

15 Regulatory Information

· Safety, health and environmental regulations/legislation specific for the substance or mixture: No further relevant information available.

(Contd. on page 11)





Safety Data Sheet (SDS)
OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

	erfund Amendments and Reauthorization): 5 (extremely hazardous substances):	
	ingredients are listed.	
· Section 313	3 (Specific toxic chemical listings):	
	barium sulphate, natural	
	1,2,4-Trimethylbenzene	
	2-butoxyethanol	
	Diethylene glycol monoethyl ether	
98-82-8	Cumene	
107-21-1	Ethylene glycol	
TSCA (Tox	ic Substances Control Act):	
7732-18-5	Water, distilled water, deionized water	ACTIVE
7727-43-7	barium sulphate, natural	ACTIVE
25322-68-3	Polyethylene Glycol	ACTIVE
95-63-6	1,2,4-Trimethylbenzene	ACTIVE
	1-methoxy-2-propanol	ACTIVE
111-76-2	2-butoxyethanol	ACTIVE
111-90-0	Diethylene glycol monoethyl ether	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light aromatic	ACTIVE
	Quartz (SiO2)	ACTIVE
	Cumene	ACTIVE
107-21-1	Ethylene glycol	ACTIVE
· Hazardous	Air Pollutants	
98-82-8 C		
	thylene glycol	
	Proposition 65:	
	known to cause cancer:	
	Quartz (SiO2)	
	Cumene	
	known to cause reproductive toxicity for females:	
	ingredients are listed.	
	known to cause reproductive toxicity for males:	
None of the	ingredients are listed.	
· Chemicals	known to cause developmental toxicity:	


25322-68-3 Polyethylene Glycol 95-63-6 1,2,4-Trimethylbenzene 107-98-2 1-methoxy-2-propanol

111-76-2 2-butoxyethanol

107-21-1 Ethylene glycol

New Jersey Right-to-Know List: 7727-43-7 barium sulphate, natural

(Contd. on page 12)



Safety Data Sheet (SDS)
OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

14808-60-7	Quartz (SiO2)	
98-82-8	Cumene	
107-21-1	Ethylene glycol	
· New Jersey	Special Hazardous Substance List:	
107-98-2	1-methoxy-2-propanol	F3
111-76-2	2-butoxyethanol	CA, F2
14808-60-7	Quartz (SiO2)	CA
98-82-8	Cumene	F3, R1
· Pennsylvar	nia Right-to-Know List:	
7727-43-7	barium sulphate, natural	
25322-68-3	Polyethylene Glycol	
95-63-6	1,2,4-Trimethylbenzene	
107-98-2	1-methoxy-2-propanol	
111-76-2	2-butoxyethanol	
14808-60-7	Quartz (SiO2)	
98-82-8	Cumene	
107-21-1	Ethylene glycol	
· Pennsylvar	nia Special Hazardous Substance List:	
95-63-6 1,	2,4-Trimethylbenzene	E
98-82-8 C	umene	E
107-21-1 E	thylene glycol	E

· Carcinogenic categories:

EPA (Envir	onmental Protection Agency):			
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(o	D, CBD(inh), NL(oral)	
95-63-6	1,2,4-Trimethylbenzene	II		
111-76-2	2-butoxyethanol	NL		
98-82-8	Cumene	D, CBD		
TLV (Thres	hold Limit Value established by ACGIH):			
111-76-2	2-butoxyethanol		A3	
14808-60-7	Quartz (SiO2)		A2	
107-21-1	Ethylene glycol		A4	
NIOSH-Ca	(National Institute for Occupational Safety and Health):			
	Quartz (SiO2)			

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).


· Hazard pictograms:





· Signal word: Warning





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

· Hazard-determining components of labeling:

Titanium Oxide

1,2,4-Trimethylbenzene

2-butoxyethanol

Solvent naphtha (petroleum), light aromatic

· Hazard statements:

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

· Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u>16 Other Information</u>

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Contact:

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration





Safety Data Sheet (SDS)
OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 01/23/2024 Reviewed on 01/23/2024

Trade Name: Rub 'n Restore Color I

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3
Flammable Liquids 4: Flammable liquids – Category 4 Acute Toxicity - Dermal 3: Acute toxicity - Category 3 Acute Toxicity - Inhalation 4: Acute toxicity - Category 4
Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B

Carcinogenicity 2: Carcinogenicity – Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Aspiration Hazard 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106